


Lined Pipe (Class 150 and Class 300)


fixed - fixed



fixed - loose



loose - loose



NPS	Length (L) mm		Length (L) Inches		Lining material		
	max.	min.	max.	min.	PTFE	PVDF	PP
1/2"	6096	65	240.0	2.56	●		
3/4"	6096	75	240.0	2.95	●		
1"	6096	75	240.0	2.95	●	●	●
1 1/4"	6096	80	240.0	3.15	●		
1 1/2"	6096	80	240.0	3.15	●	●	●
2"	6096	90	240.0	3.54	●	●	●
2 1/2"	6096	90	240.0	3.54	●	●	●
3"	6096	100	240.0	3.94	●	●	●
4"	6096	100	240.0	3.94	●	●	●
5"	6096	100	240.0	3.94	●		
6"	6096	100	240.0	3.94	●	●	●
8"	6096	120	240.0	4.72	●	●	●
10"	3048	130	120.0	5.12	●		●
12"	3048	130	120.0	5.12	●		●
14"	3048	130	120.0	5.12	●		
16"	3048	130	120.0	5.12	●		
18"	3048	130	120.0	5.12	●		
20"	2000	140	78.7	5.51	●		

Pressure Capabilities

Temperature	ANSI	ANSI
	Class 150	Class 300
100°F (38°C)	250 psig	450 psig
150°F (68°C)	242 psig	415 psig
200°F (93°C)	235 psig	390 psig
300°F (149°C)	215 psig	345 psig
400°F (204°C)	200 psig	295 psig
500°F (260°C)	170 psig	245 psig

Plastic-lined pipe and fittings with A105 flanges.

*Note: Plastic sealing faces are restricted on temperature and pressure.